



SAFECRAFT.COM

Fire
Suppression
Systems





MODEL AT

Safecraft's Model AT is completely automatic. A fast-acting thermal sensor is attached to the hose for pinpoint accuracy and a targeted response. Safecraft's unique and flexible all-metal hose targets high-risk areas remotely located away from the cylinder. Various temperature settings and hose lengths available. Safecraft offers a lightweight model for weight-critical installations and requirements.

Activation: Automatic Thermal

Size: 10 lb (*SFI-Certified*)

Agent: 3M™ Novec™ 1230 Fire Protection Fluid

Cylinder Color/Material: White or Brushed Aluminum



MODEL LM

Safecraft's Model LM is completely automatic and can include a manual backup for added protection. Fast-acting thermal sensors attached to Safecraft's unique and flexible all-metal hose targets high-risk areas remotely located away from the cylinder. Multiple sensors with several temperature settings are also available along with various hose lengths.

Activation: Automatic Thermal with Manual Backup

Size: 10 lb (*SFI-Certified*)

Agent: 3M™ Novec™ 1230 Fire Protection Fluid

Cylinder Color/Material: White Aluminum

Includes: Machined Billet Aluminum Brackets, Various Hose Lengths



MODEL LT

Safecraft's Model LT is considered the "gold standard" of the industry. More racers and professional race teams use the Model LT more than any other system. The modular design and standard features makes it the first choice for all motorsports. With its wide variety of activation and mounting options, the Model LT can be easily integrated in all vehicle designs. A super lightweight version is also available.

Activation: Single Pull, Dual Pull, Pneumatic, Electric or Electric Manual

Size: 3, 5, or 10 lb (*5 and 10 lb are SFI-Certified*)

Agent: 3M™ Novec™ 1230 Fire Protection Fluid

Cylinder Color/Material: White or Brushed Aluminum (*for 10 lb only*)



MADE IN THE USA

SAFECRAFT
SAFETY EQUIPMENT

All Safecraft systems use DOT and TC approved cylinders when required.

©2019 Safecraft, Inc. | sales@safecraft.com | 800.400.2259 | www.safecraft.com

MODEL PB2

The Model PB2 hand-held portable extinguishes fires either inside or outside the vehicle. Its unique features and mounting bracket are designed for quick responses. PULL knob, GRAB and GO. Typically mounted to any flat surface or after-market seat mount, the Model PB2's compact design offers a variety of placements.

Size: 2.5 lb

Agent: Halon 1211 Extinguishing Agent

Cylinder Color/Material: Black Wrinkle, Standard Black, White or Red Aluminum and Polished Stainless Steel

Options: Machined Billet Clear Anodized Aluminum Bracket



MODELS PB3 & PB5

Safecraft's Model PB3 / PB5 portable units are designed to mount (roll bars or flat) in various motorsport vehicles. The quick-release mechanism is custom-designed to offer versatility of placement and ease of use. Just FLIP the lever, GRAB and GO. Parts for the PB3 / PB5 and their quick-release brackets are crafted from machined billet aluminum. Unlike other extinguishers on the market, the PB3 / PB5 removable extinguishers effectively suppresses vehicle fires using a non-compacting liquid extinguishing agent.

Size: 3 or 5 lb

Agent: Halotron™ I CLEAN AGENT

Cylinder Color/Material: White or Black Wrinkle Aluminum

Options: Quick-Release Machined Billet Aluminum Bracket



MODEL SC

Safecraft's Model SC for sprint cars is completely automatic and includes a manual backup for added protection. Safecraft's unique, fast-acting thermal sensor and compact, slim design targets hard-to-reach high risk areas & tight spaces—perfect when you need 'mini' without sacrificing 'might'! The Model SC packs a powerful punch with 3M™ Novec™ 1230 Fire Protection Fluid in a 3 or 5 lb white aluminum cylinder.

Activation: Automatic Thermal with Manual Backup

Size: 3 or 5 lb

Agent: 3M™ Novec™ 1230 Fire Protection Fluid

Cylinder Color/Material: White Aluminum

Includes: Machined Billet Aluminum Brackets



MADE IN THE USA



MODELS UT3, UT5 & UT7

Safecraft's ingenuity is unveiled with this fully automatic system for the UTV market. This system provides fire suppression capability to both the engine and fuel areas. The easy-to-install kit places the thermal sensor on a flexible line routed directly to the area to be protected. Billet brackets specifically designed for mounting this system on the roll bar are included. Multiple sensor systems can be used for expanded coverage.

Activation: Automatic Thermal

Size: 3, 5 or 7 lb

Agent: 3M™ Novec™ 1230 Fire Protection Fluid

Cylinder Color/Material: White or Black Wrinkle Aluminum (*UT7 in White Only*)

Includes: Machined Billet Aluminum Brackets

INSTALLED SYSTEM WEIGHTS & DIMENSIONS

MODEL SERIES	ACTIVATION TYPE	AGENT TYPE	AGENT QTY. (Max)	OVERALL LENGTH (Max)	CYLINDER DIAMETER	NOMINAL WEIGHT
AT10	Auto Thermal	3M™ Novec™ 1230	10 lb	16.5" - 17.0"	5.25"	14 - 15. lb
LM10	Auto Thermal / Manual	3M™ Novec™ 1230	10 lb	17.0" - 18.0"	5.25"	16.5 - 17 lb
LT3	Various	3M™ Novec™ 1230	3 lb	15.3" - 15.5"	3.25"	4.5 lb
LT5	Various	3M™ Novec™ 1230	5 lb	15.5" - 16.0"	4.0"	7 lb
LT10	Various	3M™ Novec™ 1230	10 lb	17.3" - 18.0"	5.25"	15.2 lb
LX5	Pull Cable	3M™ Novec™ 1230	5 lb	15.5"	3.5" - 4.0"	6.4 - 6.7 lb
SC3	Auto Thermal / Manual	3M™ Novec™ 1230	3 lb	16.0"	3.25"	5.3 lb
SC5	Auto Thermal / Manual	3M™ Novec™ 1230	5 lb	16.5"	4.0"	7.4 lb
UT3	Auto Thermal	3M™ Novec™ 1230	3 lb	14.5"	3.25"	4.5 lb
UT5	Auto Thermal	3M™ Novec™ 1230	5 lb	15.0"	4.0"	7 lb
UT7	Auto Thermal	3M™ Novec™ 1230	7 lb	18.0"	4.0"	9.2 lb

REMOVABLE SYSTEM WEIGHTS & DIMENSIONS

MODEL SERIES	ACTIVATION TYPE	AGENT TYPE	AGENT QTY. (Max)	OVERALL LENGTH (Max)	CYLINDER DIAMETER	NOMINAL WEIGHT
PB2	Lever	Halon 1211	2.5 lb	12.4" - 13.4"	3"	3.7 - 4.4 lb
PB3	Lever	Halotron™ 1 CLEAN AGENT	3 lb	15.7"	3.25"	4.8 lb
PB5	Lever	Halotron™ 1 CLEAN AGENT	5 lb	16.7"	4.0"	7.5 lb

REMOVABLE SYSTEM ACCESSORIES NOMINAL WEIGHT

Quick Release Bracket for PB3 & PB5	1.5 lb
Billet Bracket for PB2	0.9 lb

WEST COAST HQ
 557 Clark Avenue
 Pittsburg, CA 94565
 Phone: (800) 400-2259
sales@safecraft.com

EAST COAST SERVICE CTR
 122 Knob Hill Rd
 Mooresville, NC 28117
 Phone: (704) 662-6982
sales@sriperformance.com

INT'L SERVICE CTR
 Unit 2/20 Hall Street
 St. Mary's NSW, Australia, 2760
 Phone: (+61) 2 9673 2911
jonathan@jbrcaustralia.com