



**WEIGHTS
AND
DIMENSIONS**

ORDER: 800-400-2259
SALES@SAFECRAFT.COM

Installed System Weights and Dimensions

<u>Part Number</u>	<u>Activation Type</u>	<u>Agent Qty. (LBS)</u>	<u>Cyl. Type</u>	<u>Overall Length</u>	<u>Cylinder Diameter</u>	<u>Nominal Weight</u>
AT3	Automatic Thermal	3	Slimline	14.3	3.25	4.5
AT5	Automatic Thermal	5	Slimline	14.5	4.0	7.0
AT7	Automatic Thermal	7	Slimline	18	4.0	9.2
AT10()EA	Automatic Thermal	10	Standard	18	5.25	15.1
AT10()EG	Automatic Thermal (SFI)	10	Standard	16.4	5.25	15.1
AT10()EH	Automatic Thermal (SFI)	10	Light Weight	16.4	5.25	14.1
LT3	Pull Cable	3	Slimline	15.3	3.25	4.5
	Dual Pull	3	Slimline	15.5	3.25	4.5
LT5	Pull Cable (SFI)	5	Slimline	15.5	4.0	7.0
	Dual Pull Cable (SFI)	5	Slimline	15.8	4.0	7.0
	Electric	5	Slimline	15.5	4.0	7.0
	Electric / Manual (SFI)	5	Slimline	16	4.0	7.0
LT10	Pull Cable (SFI)	10	Standard	17.3	5.25	15.2
	Dual Pull Cable (SFI)	10	Standard	17.4	5.25	15.2
	Electric	10	Standard	17.3	5.25	15.2
	Electric / Manual (SFI)	10	Standard	17.7	5.25	15.2
	Pneumatic (SFI)	10	Standard	17.5	5.25	15.2
LX5	Pull (SFI)	5	Slimline	15.5	4.0	6.7
LX5-4	Pull (SFI)	5	Lightweight	15.3	3.5	6.4

Note: Nominal weights are for the extinguisher only and does not include mount hardware or activation method.

Removable System Weights and Dimensions

PB2S	Lever	2.5	Polished Stainless	12.4	3	4.4
PB2R,W,B,BW	Lever	2.5	Pwr Coat Alum.	13.4	3	3.7
50-1410-XX Billet Brkt. For PB2						0.9
PB3	Lever	3	Pwr Coat Alum.	15.7	3.25	4.8
PB5	Lever	5	Pwr Coat Alum.	16.7	4.0	7.5
57-1700 / 1750 Quick Release Brkt. for PB3 & PB5						1.5