

**WEIGHTS
 AND
 DIMENSIONS**

Installed System Weights and Dimensions

<u>Part Number</u>	<u>Activation Type</u>	<u>Agent Qty. (LBS)</u>	<u>Cyl. Type</u>	<u>Overall Length</u>	<u>Cylinder Diameter</u>	<u>Nominal Weight</u>
AT3	Automatic Thermal	3	Slimline	14.3	3.25	4.5
AT5	Automatic Thermal	5	Slimline	14.5	4	7
AT10()EA	Automatic Thermal	10	Standard	18	5.25	15
AT10()EG	Automatic Thermal (SFI)	10	Standard	16.4	5.25	15
AT10()EH	Automatic Thermal (SFI)	10	Light Weight	16.4	5.25	14
AT10BHG-2	Automatic Thermal	10	Standard	18	5.25	16
LT3	Pull Cable	3	Slimline	15.3	3.25	4.5
	Dual Pull	3	Slimline	15.5	3.25	4.5
LT5	Pull Cable (SFI)	5	Slimline	15.5	4	7
		5	Compact	11.1	5.25	8.5
	Dual Pull Cable (SFI)	5	Slimline	15.8	4	7
		5	Compact	11.3	5.25	8.5
	Electric	5	Slimline	15.5	4	7
		5	Compact	11.1	5.25	8.5
	Electric / Manual (SFI)	5	Slimline	16	4	7
				Compact	11.5	5.25
LT10	Pull Cable (SFI)	10	Standard	17.3	5.25	15
	Dual Pull Cable (SFI)	10	Standard	17.4	5.25	15
	Electric	10	Standard	17.3	5.25	15
	Electric / Manual (SFI)	10	Standard	17.7	5.25	15
	Pneumatic (SFI)	10	Standard	17.5	5.25	15
LX5	Pull (SFI)	5	Slimline	15.5	4	6.7
LX5-4	Pull (SFI)	5	Lightweight	15.3	3.5	6.4

Removable System Weights and Dimensions

PB2S	Lever	2.5	Polished Stainless	12.4	3	4.4
PB2R,W,B,BW	Lever	2.5	Pwr Coat Alum.	13.4	3	3.7
PC2P	Lever	2.5	Stainless Steel	11.7	3	4.1
50-1410 Billet Brkt.						0.9
Wire Form Bracket for PC2						0.4